

預熱啟動式光管

傳統預熱燈管設計，點燈前一般需先以預熱電流加熱陰極燈絲，使燈絲產生熱力。採用預熱啟動方式，有助延長燈管壽命，同時降低燈觸發電壓，為最廣泛使用之燈管。



產品型號	色溫 (K)	耗電量 (W)	管形	管徑 (mm)	管長 (mm)	燈座	電流(A)	流明 (lm)	平均壽命 (小時)	演色度 (Ra)	包裝數量		光源色
											(支/內包裝)	(支/外包裝)	
直管													
FL4 D	6,500	4	T-5	15.5	134.5	G5	0.162	95	6,000	74	100	600	日光
FL4 W	4,200	4	T-5	15.5	134.5	G5	0.162	110	6,000	61	100	600	冷白光
FL4 WW	3,000	4	T-5	15.5	134.5	G5	0.162	110	6,000	60	100	600	暖白光
FL6 D	6,500	6	T-5	15.5	210.5	G5	0.147	220	7,500	74	100	600	日光
FL6 W	4,200	6	T-5	15.5	210.5	G5	0.147	245	7,500	61	100	600	冷白光
FL6 WW	3,000	6	T-5	15.5	210.5	G5	0.147	245	7,500	60	100	600	暖白光
FL8 D	6,500	8	T-5	15.5	287.0	G5	0.170	350	7,500	74	100	600	日光
FL8 W	4,200	8	T-5	15.5	287.0	G5	0.170	420	7,500	61	100	600	冷白光
FL8 WW	3,000	8	T-5	15.5	287.0	G5	0.170	420	7,500	60	100	600	暖白光
FL10 D	6,500	10	T-8	25.5	330.0	G13	0.230	440	7,500	74	25	200	日光
FL10 W	4,200	10	T-8	25.5	330.0	G13	0.230	500	7,500	61	25	200	冷白光
FL10 WW	3,000	10	T-8	25.5	330.0	G13	0.230	500	7,500	60	25	200	暖白光
FL15 D	6,500	15	T-8	25.5	436.0	G13	0.300	760	7,500	74	25	200	日光
FL15 W	4,200	15	T-8	25.5	436.0	G13	0.300	875	7,500	61	25	200	冷白光
FL15 WW	3,000	15	T-8	25.5	436.0	G13	0.300	875	7,500	60	25	200	暖白光
FL20T8D/18*	6,500	18	T-8	25.5	588.7	G13	0.370	1,090	12,000	74	---	25	日光
FL20T8W/18*	4,200	18	T-8	25.5	588.7	G13	0.370	1,200	12,000	61	---	25	冷白光
FL20T8WW/18*	3,000	18	T-8	25.5	588.7	G13	0.370	1,200	12,000	60	---	25	暖白光
FL30T8D	6,500	30	T-8	25.5	893.6	G13	0.365	2,000	12,000	74	---	25	日光
FL30T8W	4,200	30	T-8	25.5	893.6	G13	0.365	2,300	12,000	61	---	25	冷白光
FL30T8WW	3,000	30	T-8	25.5	893.6	G13	0.365	2,300	12,000	60	---	25	暖白光
FL40T8D/36*	6,500	36	T-8	25.5	1,198.0	G13	0.430	2,500	20,000	74	---	25	日光
FL40T8W/36*	4,200	36	T-8	25.5	1,198.0	G13	0.430	3,100	20,000	61	---	25	冷白光
FL40T8WW/36*	3,000	36	T-8	25.5	1,198.0	G13	0.430	3,100	20,000	60	---	25	暖白光
FL20T9D/19*	6,500	19	T-9	28.0	588.7	G13	0.350	1,070	12,000	74	---	25	日光
FL20T9W/19*	4,200	19	T-9	28.0	588.7	G13	0.350	1,230	12,000	61	---	25	冷白光
FL20T9WW/19*	3,000	19	T-9	28.0	588.7	G13	0.370	1,200	12,000	60	---	25	暖白光
FL40T9D/38*	6,500	38	T-9	28.0	1,198.0	G13	0.410	2,700	20,000	74	---	25	日光
FL40T9W/38*	4,200	38	T-9	28.0	1,198.0	G13	0.410	3,100	20,000	61	---	25	冷白光
圓管													
FCL 22D/21*	6,500	21	T-9	29	210	G10q	0.380	1,080	9,000	74	---	30	日光
FCL 22W/21*	4,200	21	T-9	29	210	G10q	0.380	1,250	9,000	61	---	30	冷白光
FCL 30D/28*	6,500	28	T-9	29	230	G10q	0.620	1,550	9,000	74	---	30	日光
FCL 30W/28*	4,200	28	T-9	29	230	G10q	0.620	1,770	9,000	61	---	30	冷白光
FCL 32D/30*	6,500	30	T-9	29	300	G10q	0.435	1,890	9,000	74	---	20	日光
FCL 32W/30*	4,200	30	T-9	29	300	G10q	0.435	2,150	9,000	61	---	20	冷白光
FCL 40D/38*	6,500	38	T-9	29	406	G10q	0.420	2,000	9,000	74	---	10	日光
FCL 40W/38*	4,200	38	T-9	29	406	G10q	0.420	2,290	9,000	61	---	10	冷白光