


TOSHIBA 東芝



投光器專用小太陽管




燈座(Lamp base)



電磁波頻譜圖(Spectral energy distribution graphs)



產品型號	標準包裝 (支/箱)	管徑 (mm)	管長 (mm)	重量 (g)	燈座	電壓 (v)	輸出功率 (w)	流明 (lm)	色溫 (k)	平均壽命 (小時)
J110V 200WA	10	8	118	7	R7s	110	200	3,400	2,950	2,000
J110V 300WA	10	8	118	7	R7s	110	300	5,900	2,950	2,000
J110V 500W	10	10	118	9	R7s	110	500	10,500	3,000	2,000
J210V 500W	10	10	118	9	R7s	210	500	9,000	2,900	2,000
J210V 500WLT	10	10	169	12	R7s	210	500	9,000	2,900	2,000
J220V 1000W	10	10	208	15	R7s	220	1,000	21,000	3,000	2,000
J220V 1500W	10	10	248	18	R7s	220	1,500	33,000	3,000	2,000



富新工程有限公司

ENGINEERING Fu Sun Engineering Limited

香港北角七姊妹道208號昌利大廈3樓302室
Room 302, 3/F, Cheong Lee Building,
No. 208 Tsat Tsz Mui Road, North Point, HK.

電話: (852)2570-8193 傳真: (852)2571-3150

電郵: enquiry@fusun-toshiba.com

網址: www.fusun-toshiba.com

中國熱線: (86) 135-60702932