


間接照明專用燈泡




用途：
適合作為裝飾。

燈座(Lamp base)



電磁波頻譜圖
(Spectral energy distribution graphs)



亮燈效果

PS 球形




G 球形




配光曲線圖


PS 球形



G 球形



產品型號	標準包裝 (支/箱)	球形	燈泡種類	管徑 (mm)	管長 (mm)	重量 (g)	燈座	輸出 功率 (w)	流明 (lm)	色溫 (k)	平均 壽命 (小時)
SILVER100V 60W	25	PS	下半身透明	60	109	32	E26	60	820	-----	1,000
SILVER100V 100W	25	A	下半身透明	70	124	46	E26	100	1,540	-----	1,000
SILVER100V 40W G95	10	G	下半身透明	95	126	52	E26	40	455	-----	2,000
SILVER100V 60W G95	10	G	下半身透明	95	126	52	E26	60	755	-----	2,000
SILVER100V 100W G95	10	G	下半身透明	95	126	52	E26	100	1,435	-----	2,000



富新工程有限公司

ENGINEERING Fu Sun Engineering Limited

香港北角七姊妹道208號昌利大廈3樓302室
Room 302, 3/F, Cheong Lee Building,
No. 208 Tsat Tsz Mui Road, North Point, HK.

電話: (852)2570-8193 傳真: (852)2571-3150

電郵: enquiry@fusun-toshiba.com

網址: www.fusun-toshiba.com

中國熱線: (86) 135-60702932